2023



# Electric Cylinder



http://www.wodtop.com



## Company Profile

## Tianyi Intelligent mainly engages in

FA factory automation parts one-stop procurement service platform; research and development, design, production, sales, and service of assembly and testing jigs, fixtures, carriers, and automation equipment (lines).

## Corporate Culture:

Mission: Through technological innovation, make factories and human life better.

Vision: To become the leading brand of a one-stop procurement service platform for


services and help enterprises take off.

FA factory automation parts; to provide intelligent equipment contract manufacturing

Values: People-oriented, consider the benefits to others; start with the end in mind,

take responsibility and strive; adapt to changes, innovate with technology.

## Research and Patents for Competitive Advantage



Full-time R&D personnel:170 01 Bachelor's degree or above: 35 people Practical R&D Type: 135 people Ability to resolve technical issues on-site within 2-6 hours R&D system 02 Two types of platforms: standard parts and non-standard automation equipment A system: three-dimensional R&D framework Three directions: parts, product process, non-standard equipment Patent Protection System 03 Invention Patents: 6 Utility model patents: 43 Design patents: 13; software copyrights: 10.

## Contents

1. Introduction to Servo Electric Cylinder	<del></del> 01
2. Electric cylinder quick selection	03
3. Electric cylinder model description	05
4. WTA Performance Specifications Table	06
5. WTB Performance Specifications	07
6. WTA 40	08
7. WTA 50	
8. WTA 60	14
9. WTA 75	17
10.WTA80	20
11.WTA94	23
12.WTA110	26
13.WTA132	29
14.WTB120	32
15.WTB140	34
16.WTB160	36
17.WTB220	
18.WTT160	40
19.WTT220	42
20.WTT270	44
21. Calculation method for selecting a servo electric cylinder —	<del></del> 46
22. Electric Cylinder Selection Table	47



#### The principle of the servo electric cylinder

Servo electric cylinders are modular products that integrate servo motors with ball screws. They convert the rotational motion of the servo motor into linear motion while transforming the servo motor's optimal advantages—precise speed control, precise rotation control, and precise torque control—into precise speed control, precise position control, and precise thrust control. They represent a revolutionary product series for achieving high-precision linear motion. They are widely used in material handling, high-precision mechanical manufacturing fields, such as aerospace testing equipment, six-degree-of-freedom simulators, robots, injection molding machines, mold control, valve control, precision machine tools, and automobile manufacturing equipment.



#### High-Performance Products: Features of Servo Electric Cylinders

The servo electric cylinder can operate reliably for long periods in harsh environments, achieving high-intensity, high-speed, and high-precision motion. It ensures smooth movement with low noise, and its unique anti-rotation feature guarantees high-precision position control and enhanced safety for the equipment.

#### The Optimal Alternatives to Hydraulic and Pneumatic Cylinders

Servo electric cylinders can completely replace hydraulic and pneumatic cylinders, offering advantages such as a more environmentally friendly, energy-efficient, and cleaner operation. They can easily connect with control systems such as PLCs, enabling high-precision motion control.

#### Harsh environment

The protection level of the servo electric actuator can reach IP55 and IP66, allowing it to operate normally in harsh outdoor environments. Therefore, it can be widely applied in industries such as paper manufacturing, chemical processing, and welding.

#### WT Features of the Series Servo Electric Actuators

Thrust range: 10kg to 50 tons

Stroke can reach 3m, 100% duty cycle

Speed up to 1000mm/s

Imported precision-grade ground ball screw, high efficiency, non-

locking.

Equipped with imported servo motors and stepper motors from various brands.

Linear scales can be added to achieve closed-loop servo control, with positional accuracy reaching 0.01mm and precise thrust control, the thrust accuracy is 5%, and with the addition of pressure sensors, the control accuracy is 1%.

It enables precise speed control, with high performance at both high and low speeds.

Stable thrust can be maintained at any position.

High dynamic response time, high acceleration.

High rigidity, impact resistance.

Ultra-long service life, simple operation and maintenance, low noise.

#### Low-Cost Maintenance

The servo electric cylinder requires only periodic lubrication in complex environments and has no easily worn parts that need maintenance or replacement, significantly reducing after-sales service costs compared to hydraulic systems.

#### **Flexibility**

It provides highly flexible installation configurations and a complete range of installation components: front flanges, rear flanges, side flanges, rear hinges, trunnion mounts, guide modules, and more; it can be installed directly with a servo motor either in a linear configuration or in parallel; various accessories can be added, such as limit switches, planetary gear reducers, and preloaded nuts; drive options include AC brake motors, DC motors, stepper motors, and servo motors from various manufacturers.









#### Overview of Servo Electric Cylinder Specifications (Quick Selection)

#### WTA Series of Aluminum-Based Electric Cylinders

Servo Electric Actuator Series	Cylinder block external dimensions (mm)	Bore Diameter	Recommended Maximum Thrust (kN)	Maximum Speed (mm/s)	Maximum travel (mm)	Lead of the Screw (mm)					
VA/TA 40 (Aluminum-	Square: 44.5*44.5,Circle:	22	0.2	100	300	2					
WTA 40 <sup>(Aluminum-</sup> based)	Customizable	32	0.7	200	600	4					
WTA 50 (Aluminum- based)	Square: 53*53,Round:	40	1.5	250	600	5					
based)	Customizable	40	1.5	500	600	10					
			5.0	250	800	5					
WTA 60 <sup>(Aluminum-</sup> based)	Square: 61*61,Circle: Customizable	50	4.0	500	800	10					
			0.5	800	800	16					
			8.0	250	1050	5					
WTA 75 (Aluminum- based)	Square: 75*75,Circular: Customizable	63	8.0	500	1050	10					
			2.0	1000	1050	20					
			10.0	250	1500	5					
WTA 80 (Aluminum- based)	Square: 80*80,Circular: Customizable	65	15.0	500	1500	10					
			2.0	1250	1500	25					
			12.0	166	1800	5					
WTA 94 (Aluminum- based)	Square: 94*94,Circular: Customizable	80	80	80	80	80	80	30.0	333	1800	10
			8.0	666	1800	20					
WTA 110 <sup>(Aluminum-based)</sup>	Square: 110*110,Circular:	100	100	100	100	100	100	40.0	250	1800	10
based)	Customizable	100	10.0	500	1800	20					
(Aluminum- WTA 132 based)	Square: 132*132,Circle:	125	50.0	250	2000	10					
vv i A 132 based)	Customizable	125	70.0	250	2000	20					

#### WTB Series Steel-Based Electric Cylinder

Servo Electric Actuator Series	Cylinder Block SectionOverall Dimensions (mm)	Bore Diameter	Recommended Maximum Thrust (kN)	Maximum Speed (mm/s)	Maximum Travel (mm)	Lead of the Screw (mm)
WTB 120 (Steel-	Circle:Φ120	100	40	250	1000	10
based)	Olf 010. 4 120	100	20	250	1000	20
(Steel-	Circle:Φ140	120	50	250	1000	10
WTB 140 (based)	Circle. \$140	120	70	250	1000	20
WTP 400 (Steel-	Circle:Φ168	140	60	125	1000	10
WTB 160 (Steel-based)	Circle: Ф 168	140	120	125	1000	20
WTB 220 (Steel- based)	Circle:Φ220	200	200	50	1000	20

#### WTT Series of Heavy-Duty Electric Cylinders

Servo Electric Actuator Series	Cylinder Block SectionOverall Dimensions (mm)	Bore Diameter	Recommended Maximum Thrust (kN)	Maximum Speed (mm/s)	Maximum Travel (mm)	Lead of the Screw (mm)
WTT 160 (Steel-	Circle:Φ180	140	150	40	1000	16
based)	Officie. 4 100	140	200	50	1000	20
(Steel-	Circle:Φ235	200	250	40	1000	16
WTT 220 (dicci-	Circle. 4235	200	300	50	1000	20
WITT 070 (Steel-	/TT 270 (Steel-	220	400	40	1000	16
WTT 270 (oleci-	Circle. 4273	220	500	50	1000	20


#### WTD Series of Electric Actuators

Model	Input Voltage(V <sub>∞</sub> )	Outer Diameter	Maximum Thrust (kN)	Maximum Speed (mm/s)	Maximum Travel (mm)	Lead of the Screw (mm)
			2.6	40	1000	5
WITDS COD	12/24	60*60	4.5	24	1000	5
WTDS 60B	12/24	60 60	6.8	18	1000	5
			10.0	11	1000	5
WTDC 60A	12/24/26	<b>+</b> C0	1.1	54	1000	5
WIDCOUA	12/24/36	ф60	2.25	30	1000	5
			2.25	61	1000	5
WTDC 60B	12/24/36	ф60	4.5	30	1000	5
			6.8	15	1000	5
			2.6	40	1000	5
WTDN 60B	12/24	60*60	4.5	24	1000	5
VVIDIVOUD	60B 12/24	00 00	6.8	18	1000	5
			10.0	11	1000	5

Note: 1. For special operating conditions, such as extremely harsh environments, ultra-high frequencies, extended service life, or excessive loads, please consult our technical engineering staff. 2. Maximum thrust and maximum speed cannot be achieved simultaneously.

### **Electric Cylinder Model Description**

#### **Description of Servo Electric Cylinder Models**



## WTA Performance Specification Sheet

#### Performance Specification Table of Aluminum Servo Electric Cylinder:

Product Series	WTA	<b>\</b> 40	WTA	<b>\</b> 50	WT	<b>4</b> 60	WT	<b>4</b> 75		<b>WTA</b> 80			<b>WTA</b> 94		WTA	110	WTA	132
Ball Screw Lead (mm)	2	4	5	10	5	10	5	10	5	10	20	5	10	20	10	20	10	20
Rated Thrust (kN)	0.2	0.7	1.5	1.5	5	4	8	8	10	15	2	12	30	8	40	10	50	70
Rated Speed (mm/s)	100	200	250	500	250	500	250	500	166	333	666	208	417	833	283	500	225	500
Rated Thrust Ball Screw Input Torque (Nm)	0.28	0.28	0.54	0.54	5.52	10.7	5.52	10.7	9.4	28.75	23.4	12.4	37.2	49.7	61.92	66.34	98.4	131.3
Ball Screw Basic Dynamic Load (kN)	4.7	4.7	7.6	7.5	13.8	11	13.8	11	15.5	29.5	13.8	19.2	48	19	53.9	39.5	60	71
Rotational Inertia of Parallel Cylinder (kg·m²·10⁴)	0.0215	0.0415	0.0435	0.0435	0.1	0.18	0.1	0.18	1.388	2.409	2.209	3.563	5.698	6.036	14.61	14.913	78.913	79.609
Rotational Inertia of Linear Cylinder Block (kg·m²·10 <sup>-3</sup> )	0.0145	0.0245	0.0265	0.0265	0.08	0.09	0.08	0.09	0.763	0.784	0.584	3.006	4.569	5.874	5.418	5.721	32.793	33.489
Rotational Inertia per 100 min (kg·m²·10⁴)	0.0095	0.0165	0.0185	0.0185	0.052	0.056	0.052	0.056	0.303	0.309	0.203	1.023	1.069	1.127	1.989	2.041	4.83	4.83
Maximum Stroke (mm)	400	400	600	600	80	00	10	50		1500			1500		18	00	18	00
Maximum Input Speed (rpm)	5000	5000	30	00	30	00	30	00		2750			2500		15	00	15	00
Cylinder Block Weight (without Motor) (kg)	0.9	1	1.	43	2.32	2.32	3.2	3.2	6.42	6.54	6.32	9.9	10.9	9.9	15.63	15.63	65	65
Cylinder Block Folded Weight (without Motor) (kg)	1.1	1.2	1	9	2.51	2.51	2.51	2.51	6.65	7.54	6.35	10.6	11.6	10.6	16.93	16.93	71	71
Weight per 100mm Stroke (kg)	0.4	0.45	0.	68	0.98	0.98	0.98	0.98	1.13	1.13	1.13	2	2	2	2.9	2.9	4.8	4.8
								V	VTA/B: E	all Screv	V							
Internal Mechanical Mechanism								WT	T:Heavy	-Duty Sc	rew							
								WTX:	Planetar	y Roller S	Screw							
Maximum Idle Rotation Angle of Power Tube (°)	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1
Class P5 Steering Clearance (mm)	0.01- 0.02																	
Class P7 Steering Clearance (mm)	0.02- 0.04																	
Class P7 300mm Lead Error (mm)	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05
Class P5 300mm Lead Error (mm)	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023
Class P7 Repeat Positioning Accuracy	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02
Class P5 Repeat Positioning Accuracy	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01

## **WTB** Performance Parameter Table

#### Performance Parameter Table of Steel Servo Electric Cylinder

Product Series	WTB	<b>3</b> 120	WTB	<b>3</b> 140	WTE	<b>3</b> 160	<b>WTB</b> 220	wm	T160	WTT	220	WTT	270
Ball Screw Lead (mm)	10	20	10	20	10	20	20	16	20	16	20	16	20
Rated Thrust (kN)	40	20	50	70	60	100	200	150	200	250	300	400	500
Rated Speed (mm/s)	333	666	283	500	250	50	50	57	50	57	50	57	50
Rated Thrust Ball Screw Input Torque (Nm)	28.75	108.06	90.05	144.09	108.06	360.23	891.3	665	891.3	1114.1	1337	1559.8	1782.6
Ball Screw Basic Dynamic Load (kN)	50.3	39.3	60	57.4	67.1	114.4	224.2	368.00	388.00	426.00	456.00	550.00	557.00
Rotational Inertia of Parallel Cylinder (kg·m²·10⁴)	14.61	14.913	78.913	79.609	195.56	205.24	250.69	195.56	205.24	220.36	250.69	420.36	450.69
Rotational Inertia of Linear Cylinder Block (kg·m²·10⁴)	5.418	5.721	32.793	33.489	150.53	164.63	220.45	150.53	164.63	210.58	220.45	410.58	420.45
Rotational Inertia per 100 min (kg·m²·10⁴)	1.989	2.041	12.21	12.21	21.74	21.85	45.32	31.74	31.74	45.32	45.32	65.32	65.25
Maximum Stroke (mm)	10	00	10	00	10	00	1000	10	00	10	00	10	00
Maximum Input Speed (rpm)	20	00	15	00	750	150	150	214	150	214	150	214	150
Cylinder Block Weight (without Motor) (kg)	32.5	32.5	65.4	65.4	112	112	258	132	132	278	278	381	381
Cylinder Block Folded Weight (without Motor) (kg)	31.2	31.2	66.6	66.6	136	136	295	156	156	315	315	406	406
Weight per 100mm Stroke (kg)	4.3	4.3	7.5	7.5	10.2	10.2	18	10.2	10.2	18	18	26	26
						W	TB: Ball Scr	ew					
Internal Mechanical Mechanism						WTT:	Heavy-Duty	Screw					
						WTX:Pla	netary Rolle	r Screw					
Maximum Idle Rotation Angle of Power Tube (°)	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1
Class P5 Steering Clearance (mm)	0.01-0.02	0.01-0.02	0.01-0.02	0.01-0.02	0.01-0.02	0.01-0.02	0.01-0.02	0.01-0.02	0.01-0.02	0.01-0.02	0.01-0.02	0.01-0.02	0.01-0.02
Class P7 Steering Clearance (mm)	0.02-0.04	0.02-0.04	0.02-0.04	0.02-0.04	0.02-0.04	0.02-0.04	0.02-0.04	0.02-0.04	0.02-0.04	0.02-0.04	0.02-0.04	0.02-0.04	0.02-0.04
Class P7 300mm Lead Error (mm)	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05
Class P5 300mm Lead Error (mm)	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023	0.023
Class P7 Repeat Positioning Accuracy	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02
Class P5 Repeat Positioning Accuracy	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01


## WTA 40 Series Servo Electric Cylinder





#### Selection Parameters Table for Servo Electric Cylinders

	Series and Model					<b>WTA</b> 40						
0	Lead of Lead Screw (mm)		2			2.5			4			
Specification	Electric Cylinder Thrust Range (kN)					0.01 ~ 0.4						
	Selectable Stroke of Electric Cylinder (mm)		20、30、5	0、80、10	0、150、20	00、250、3	300、350、	400、450、	500、600			
	Туре			Di	rect Connec	tion Type, F	olding Type					
	Reduction Ratio (i)		Direct Connection Type, Folding Type       1:1       2.22     2.21     16.49       0.1     0.2     0.4     0.1     0.2     0.4									
Indicator Input	Rated Dynamic Load of Lead Screw (kN)		2.22			2.21			16.49			
mulcator imput	Motor Rated Power (kW)	0.1	0.2	0.4	0.1	0.2	0.4	0.1	0.2	0.4		
	Motor Rated Torque (N·m)	0.32	2.22     2.21     16.49       0.1     0.2     0.4     0.1     0.2     0.4     0.1     0.2     0.0									
	Motor Rated Speed (rpm)					3000						
	Electric Cylinder Rated Thrust (kN)	0.9	1.8	3.5	0.7	1.4	2.8	0.4	0.9	1.8		
Output Indicator	Electric Cylinder Rated Speed (mm/s)	100	100	100	125	125	125	200	200	200		
	Recommended Maximum Load (kN)		0.2			0.3			0.7			

If a reduction ratio needs to be added, the above output parameters shall be directly converted by the reduction ratio multiple.
 For the specific usage of the WTA40 Electric Cylinder, please consult with our company's engineers.







## WTA 50 Series Servo Electric Cylinder








#### Selection Parameters Table for Servo Electric Cylinders

	Series and Model						<b>WTA</b> 50				
	Lead of Lead Screw (mm)		4				5			10	
Specification	Electric Cylinder Thrust Range (kN)						0.01 ~ 1				
	Electric Cylinder Selectable Stroke (mm)		20、30、	50、	80、10	0、150、2	00、250、3	300、350、	400、450、	500、600	
	Туре				[	Direct Conr	ection Type	e, Folding T	уре		
	Reduction Ratio (i)						1:1				
Indicator	Basic Dynamic Axial Load Rating (kN)		9.02				6.61			6.42	
Input	Rated Power (kW)	0.1	0.2		0.4	0.1	0.2	0.4	0.1	0.2	0.4
	Motor Rated Torque (N·m)	0.32	0.64		1.27	0.32	0.64	1.27	0.32	0.64	1.27
	Motor Rated Speed (rpm)						3000				
	Electric Cylinder Rated Thrust (kN)	0.4	0.9		1.8	0.4	0.7	1.4	0.2	0.4	0.7
Output Indicators	Electric Cylinder Rated Speed (mm/s)	200	200		200	250	250	250	500	500	500
	Recommended Maximum Load (kN)		1.5				1.5			1.5	

<sup>1.</sup>If a reduction ratio is required, the above output parameters shall be directly converted by the reduction ratio multiple. 2.For the specific usage of the WTA50 Electric Cylinder, please consult with our company's engineers.








## WTA 60 Series Servo Electric Cylinder





#### Selection Parameters Table for Servo Electric Cylinders

	Series and Model							WT	<b>A</b> 60						
Specification	Lead of Lead Screw (mm)		į	5				1	0				16		
	Electric Cylinder Thrust Range (kN)							0.01 ^	<b>~</b> 4.49						
	Electric Cylinder Selectable Stroke (mm)	10、	20、30	、50、	80、100、	150、	200、	250、	300、	350、400	、450、	500、	600、	700、	800
	Туре					Dir	ect Co	onnec	tion Typ	e, Foldin	ј Туре				
	Reduction Ratio (i)		1:1 13.8 11.03 10.73												
Indicator	Basic Dynamic Axial Load Rating (kN)		13	3.8				11	.03		10.73				
Input	Rated Power (kW)	0.2	0.4	0.75	1	0.2		0.4	0.75	1	0.2	0.	4	0.75	1
	Motor Rated Torque (N·m)	0.64	1.27	2.39	3.18	0.64	4 :	1.27	2.39	2.18	0.64	1.2	27	2.39	3.18
	Motor Rated Speed (rpm)					•		30	00						
Output	Electric Cylinder Rated Thrust (kN)	0.7	1.4	2.7	3.5	0.4		0.7	1.3	1.8	0.2	0.	4	0.8	1.1
Indicators	Electric Cylinder Rated Speed (mm/s)         250         250         250         250         500         500         500         800         800         800									800					
	Recommended Maximum Load (kN)		į	5				2	1				0.5		

1.If a reduction ratio is required, the above output parameters shall be directly converted by the reduction ratio multiple. 2.For the specific usage of the WTA60 Electric Cylinder, please consult with our company's engineers.








## WTA75 Series Servo Electric Cylinder





#### Selection Parameters Table for Servo Electric Cylinders

	Series and Model						WT	<b>A</b> 75						
Specification	Lead of Lead Screw (mm)		į	5			1	.0				20		
	Electric Cylinder Thrust Range (kN)						0.01	~ 10						
	Electric Cylinder Selectable Stroke (mm)	20、3	0、50、	80、100	、150、2	200、25		350、4 00	00、450、	500、	600、70	0、800、	900、	
	Туре					Direct C	onnectio	n Type,	Folding 1	Гуре				
	Reduction Ratio (i)		1:1											
Indicator	Basic Dynamic Axial Load Rating (kN)		1	.5			1	.5			1.38			
Input	Rated Power (kW)	0.4	0.75	1	1.5	0.4	0.75	1	1.5	0.4	0.75	1	1.5	
	Motor Rated Torque (N·m)	1.27	2.39	3.18	4.775	1.27	2.39	3.18	4.775	1.27	2.39	3.18	4.775	
	Motor Rated Speed (rpm)						30	00						
Output	Electric Cylinder Rated Thrust (kN)	1.4	2.7	3.5	5.3	0.7	1.3	1.8	2.7	0.4	0.7	0.9	1.3	
ndicators	Electric Cylinder											1000		
	Recommended Maximum Load (kN)			3			8	3				2		

1.If a reduction ratio is required, the above output parameters shall be directly converted by the reduction ratio multiple. 2.For the specific usage of the WTA75 Electric Cylinder, please consult with our company's engineers.







## WTA 80 Series Servo Electric Cylinder








#### Selection Parameters Table for Servo Electric Cylinders

	Series and Model						WT	<b>4</b> 80					
	Lead of Lead Screw (mm)			5			1	0			2	0	
Specification	Electric Cylinder Thrust Range (kN)						0.01	~ 15					
	Electric Cylinder Selectable Stroke (mm		30、50、	80、100			0、300、 )、1200、				00、700	、800、!	900、
	Туре					Direct C	Connectio	n Type,	Folding 1	Гуре			
	Reduction Ratio (i)		1:1										
Indicator Input	Basic Dynamic Axial Load Rating (kN)		17	.24			29	.54			0.8	343	
Input	Rated Power (kW)	0.75	1	1.5	2	0.75	1	1.5	2	0.75	1	1.5	2
	Motor Rated Torque (N·m)	2.39	3.18	7.16	9.55	2.39	3.18	7.16	9.55	2.39	3.18	7.16	9.55
	Motor Rated Speed (rpm)	30	00	20	00	30	00	20	00	30	00	20	00
0.11	Electric Cylinder Rated Thrust (kN)	2.7	3.5	8.0	10.6	1.3	1.8	4.0	5.3	0.7	0.9	2.0	2.7
Output Indicators											666		
4 If a needs	Recommended Maximum Load (kN)		_	.0	- h - ll h -	alima a Alba	_	5	lti	t:	_	2	

1.If a reduction ratio is required, the above output parameters shall be directly converted by the reduction ratio multiple. 2.For the specific usage of the WTA80 Electric Cylinder, please consult with our company's engineers.







## WTA 94 Series Servo Electric Cylinder








#### Selection Parameters Table for Servo Electric Cylinders

Specification	Series and Model						WT	<b>4</b> 94					
	Lead of Lead Screw (mm)		ļ	5		10				20			
	Electric Cylinder Thrust Range (kN)		0.01 ~ 25										
	Electric Cylinder Selectable Stroke (mm)	50、	50、80、100、150、200、250、300、350、400、450、500、600、700、800、1000、1100、 1200、1300、1400、1500										
	Туре		Direct Connection Type, Folding Type										
	Reduction Ratio (i)		1:1										
Indicator	Basic Dynamic Axial Load Rating (kN)		19	.22		48.05				19.07			
Input	Rated Power (kW)	1	1.5	2	3.5	1	1.5	2	3.5	1	1.5	2	3.5
	Motor Rated Torque (N·m)	4.77	7.16	9.55	16.71	3.18	7.16	9.55	16.71	3.18	7.16	9.55	16.71
	Motor Rated Speed (rpm)	2000											
Output	Electric Cylinder Rated Thrust (kN)	5.3	8.0	10.6	18.6	1.8	4.0	5.3	9.3	0.9	2.0	2.7	4.6
Indicators	Electric Cylinder Rated Speed (mm/s)	166	166	166	166	333	333	333	333	666	666	666	666
	Recommended Maximum Load (kN)		12 30									3	

1.If a reduction ratio is required, the above output parameters shall be directly converted by the reduction ratio multiple. 2.For the specific usage of the WTA94 Electric Cylinder, please consult with our company's engineers.







## WTA 110 Series Servo Electric Cylinder








#### Selection Parameters Table for Servo Electric Cylinders

Specification	Series and Model				WTA	110					
	Lead of Lead Screw (mm)		1	.0		20					
	Electric Cylinder Thrust Range (kN)				0.01	~ 40					
	Electric Cylinder Selectable Stroke (mm)		100、150、		00、350、40 1200、1300、			、800、1000	、1100、		
	Туре										
	Reduction Ratio (i)										
Indicator	Basic Dynamic Axial Load Rating (kN)		53	3.9							
Input	Rated Power (kW)	2	3	3.5	5.5	2	3	3.5	5.5		
	Motor Rated Torque (N⋅m)	9.55	14.32	16.71	35.01	9.55	14.32	16.71	35.01		
	Motor Rated Speed (rpm)		2000		1500		2000		1500		
Output	Electric Cylinder Rated Thrust (kN)	5.3	8.0	9.3	19.4	2.7	4.0	4.6	9.7		
Output Indicators	Electric Cylinder Rated Speed (mm/s)	333.33	333	333	250	666.66	667	667	500		
	Recommended Maximum Load (kN)		4	10			1	0			

1.If a reduction ratio is required, the above output parameters shall be directly converted by the reduction ratio multiple. 2.For the specific usage of the WTA110 Electric Cylinder, please consult with our company's engineers.








## WTA 132 Series Servo Electric Cylinder





#### **Selection Parameters Table for Servo Electric Cylinders**

	Series and Model				WTA	<b>1</b> 132						
Specification	Lead of Lead Screw (mm)		1	.0		20						
	Electric Cylinder Thrust Range (kN)		0 ~ 50									
	Electric Cylinder Selectable Stroke (mm)	50、80、	100、150、2	200、250、30 1200		0、450、500 00、1500、1		、800、1000	)、1100、			
	Туре		Direct Connection Type, Folding Type									
	Reduction Ratio (i)											
Indicator	Basic Dynamic Axial Load Rating (kN)		67	7.1		71.4						
Input	Rated Power (kW)	3	4.5	5.5	7.5	3	4.5	5.5	7.5			
	Motor Rated Torque (N·m)	19.1	28.65	35.01	47.74	19.1	28.65	35.01	47.74			
	Motor Rated Speed (rpm)	1500										
	Electric Cylinder Rated Thrust (kN)	10.6	15.9	19.4	26.5	10.6	15.9	19.4	26.5			
Output Indicators	Electric Cylinder Rated Speed (mm/s)	250	250	250	250	500	500	500	500			
	Recommended Maximum Load (kN)		5	50		70						

1.If a reduction ratio is required, the above output parameters shall be directly converted by the reduction ratio multiple. 2.For the specific usage of the WTA132 Electric Cylinder, please consult with our company's engineers.








## WTB 120 Series Servo Electric Cylinder




#### Selection Parameters Table for Servo Electric Cylinders

Specification	Series and Model				WTE	<b>3</b> 120								
	Lead of Lead Screw (mm)		1	0		20								
	Electric Cylinder Thrust Range (kN)		0.01 ~ 40											
	Electric Cylinder Selectable Stroke (mm)		$0\sim 1000$											
	Туре		Direct Connection Type, Folding Type											
	Reduction Ratio (i)				1	:1								
Indicator	Basic Dynamic Axial Load Rating (kN)		53	3.9		39.6								
Input	Rated Power (kW)	2	3	3.5	5.5	2	3	3.5	5.5					
	Motor Rated Torque (N·m)	9.55	14.32	16.71	35.01	9.55	14.32	16.71	35.01					
	Motor Rated Speed (rpm)		2000		1500	2000			1500					
	Electric Cylinder Rated Thrust (kN)	5.3	8.0	9.3	19.4	2.7	4.0	4.6	9.7					
Output Indicators	Electric Cylinder Rated Speed (mm/s)	333.33	333	333	250	666.66	667	667	500					
	Recommended Maximum Load (kN)		4	0		20								

<sup>1.</sup>If a reduction ratio is required, the above output parameters shall be directly converted by the reduction ratio multiple. 2.For the specific usage of the WTB120 Electric Cylinder, please consult with our company's engineers.




# WTB 140 Series Servo Electric Cylinder




	Series and Model		<b>WTB</b> 140								
Specification	Lead of Lead Screw (mm)		1	0		20					
	Electric Cylinder Thrust Range (kN)		0 ~ 60								
	Electric Cylinder Selectable Stroke (mm)		0 ~ 1000								
	Туре		Direct Connection Type, Folding Type								
	Reduction Ratio (i)	1:1									
Indicator	Basic Dynamic Axial Load Rating (kN)	67.1				71.4					
Input	Rated Power (kW)	3	4.5	5.5	7.5	3	4.5	5.5	7.5		
	Motor Rated Torque (N·m)	19.1	28.65	35.01	47.74	19.1	28.65	35.01	47.74		
	Motor Rated Speed (rpm)				00						
	Electric Cylinder Rated Thrust (kN)	10.6	15.9	19.4	26.5	5.3	8.0	9.7	13.3		
Output Indicators	Electric Cylinder Rated Speed (mm/s)	250	250	250	250	0	500	500	500		
	Recommended Maximum Load (kN)		5	0		70					

<sup>1.</sup>If a reduction ratio is required, the above output parameters shall be directly converted by the reduction ratio multiple. 2.For the specific usage of the WTB140 Electric Cylinder, please consult with our company's engineers.




# WTB 160 Series Servo Electric Cylinder



	Series and Model		<b>WTB</b> 160									
Specification	Lead of Lead Screw (mm)		1	0		20						
	Electric Cylinder Thrust Range (kN)		0.01 ~ 100									
	Electric Cylinder Selectable Stroke (mm)		$50\sim 1000$									
	Туре		Direct Connection Type, Folding Type									
	Reduction Ratio (i)				1	1:1						
Indicator Input	Basic Dynamic Axial Load Rating (kN)		67	.19		114.44						
mpat	Rated Power (kW)	5.5	7.5	11	15	5.5	7.5	11	15			
	Motor Rated Torque (N·m)	35.01	47.74	70	95.4	35.01	47.74	70	95.4			
	Motor Rated Speed (rpm)				15	00						
	Electric Cylinder Rated Thrust (kN)	19.4	26.5	38.9	53.0	9.7	13.3	19.4	26.5			
Output ndicators	Electric Cylinder Rated Speed (mm/s)	250	250	250	250	500	500	500	500			
	Recommended Maximum Load (kN)		6	0		120						

<sup>1.</sup>If a reduction ratio is required, the above output parameters shall be directly converted by the reduction ratio multiple. 2.For the specific usage of the WTB160 Electric Cylinder, please consult with our company's engineers.




# WTB220 Series Servo Electric Cylinder



	Series and Model		<b>WTB</b> 220								
Specification	Lead of Lead Screw (mm)		2	0		20					
	Electric Cylinder Thrust Range (kN)		0.01 ~ 200								
	Electric Cylinder Selectable Stroke (mm)		50 ~ 1000								
	Туре		Direct Connection Type, Folding Type								
	Reduction Ratio (i)				1	1:1					
Indicator	Basic Dynamic Axial Load Rating (kN)		15	1.0		224.2					
Input	Rated Power (kW)	7.5	11	15	22	7.5	11	15	22		
	Motor Rated Torque (N·m)	48	70	95.5	140	48	70	95.5	140		
	Motor Rated Speed (rpm)				15	00					
	Electric Cylinder Rated Thrust (kN)	13.3	19.4	26.5	38.9	13.3	19.4	26.5	38.9		
Output Indicators	Electric Cylinder Rated Speed (mm/s)	500	500	500	500	500	500	500	500		
	Recommended Maximum Load (kN)		15	50		200 0.4			.4		

<sup>1.</sup>If a reduction ratio is required, the above output parameters shall be directly converted by the reduction ratio multiple. 2.For the specific usage of the WTB220 Electric Cylinder, please consult with our company's engineers.




# WTT 160 Series Servo Electric Cylinder




	Series and Model				WTT	160					
Specification	Lead of Lead Screw (mm)		1	6		20					
	Electric Cylinder Thrust Range (kN)		0.01 ~ 200								
	Electric Cylinder Selectable Stroke (mm)		50 ~ 1000								
	Туре		Direct Connection Type, Folding Type								
	Reduction Ratio (i)				1	::1					
Indicator Input	Basic Dynamic Axial Load Rating (kN)		36	8.0		388.0					
	Rated Power (kW)	7.5	11	15	22	7.5	11	15	22		
	Motor Rated Torque (N⋅m)	48	70	95.5	140	48	70	95.5	140		
	Motor Rated Speed (rpm)				15	00					
	Electric Cylinder Rated Thrust (kN)	16.5	24.3	33.1	48.6	13.2	19.4	26.5	38.8		
Output Indicators	Electric Cylinder Rated Speed (mm/s)	400	400	400	400	500	500	500	500		
	Recommended Maximum Load (kN)		1!	50		200					

<sup>1.</sup>If a reduction ratio is required, the above output parameters shall be directly converted by the reduction ratio multiple. 2.For the specific usage of the WTT160 Electric Cylinder, please consult with our company's engineers.




# WTT 220 Series Servo Electric Cylinder




	Series and Model				WTT	220					
Specification	Lead of Lead Screw (mm)		1	6		20					
	Electric Cylinder Thrust Range (kN)		0.01 ~ 300								
	Electric Cylinder Selectable Stroke (mm)		50 ~ 1000								
Indicator	Туре		Direct Connection Type, Folding Type								
	Reduction Ratio (i)	1:1									
	Basic Dynamic Axial Load Rating (kN)		42	26		456					
Input	Rated Power (kW)	11	15	22	30	11	15	22	30		
	Motor Rated Torque (N·m)	70	95.5	140	191	70	95.5	140	191		
	Motor Rated Speed (rpm)				15	00					
	Electric Cylinder Rated Thrust (kN)	24.3	33.1	48.6	66.2	19.4	26.5	38.8	53		
Output Indicators	Electric Cylinder Rated Speed (mm/s)	400	400	400	400	500	500	500	500		
	Recommended Maximum Load (kN)		25	50		300					

<sup>1.</sup>If a reduction ratio is required, the above output parameters shall be directly converted by the reduction ratio multiple. 2.For the specific usage of the WTT220 Electric Cylinder, please consult with our company's engineers.




# WTT 270 Series Servo Electric Cylinder



	Series and Model				WTT	270					
Specification	Lead of Lead Screw (mm)		1	6		20					
opeanoation	Electric Cylinder Thrust Range (kN)		0.01 ~ 500								
	Electric Cylinder Selectable Stroke (mm)		50 ~ 1000								
	Туре		Direct Connection Type, Folding Type								
	Reduction Ratio (i)				:1						
Indicator	Basic Dynamic Axial Load Rating (kN)		5!	50		557					
Input	Rated Power (kW)	15	20	30	45	15	20	30	45		
	Motor Rated Torque (N·m)	95.5	140	191	286	95.5	140	191	286		
	Motor Rated Speed (rpm)		1500								
	Electric Cylinder Rated Thrust (kN)	24.3	33.1	48.6	99.4	26.5	38.8	53	99.4		
Output Indicators	Electric Cylinder Rated Speed (mm/s)	400	400	400	400	500	500	500	500		
	Recommended Maximum Load (kN)		40	00		500					

<sup>1.</sup>If a reduction ratio is required, the above output parameters shall be directly converted by the reduction ratio multiple. 2.For the specific usage of the WTT270 Electric Cylinder, please consult with our company's engineers.



# Calculation Method for Selecting Servo Electric Cylinders

### Calculation of Electric Cylinder Output Force

The Relationship between Motor Output Torque and Electric Cylinder Output Force

$$F = \frac{T X \eta X 2\pi X R}{L}$$

F: Electric Cylinder Output Force (kN) T: Motor Output Torque (N·m) R: Reduction Ratio L: Lead Screw Lead (mm)  $\eta$ : Mechanical Efficiency (The general recommended value is 85%, but the efficiency value is related to actual working conditions and may also change. Please make corresponding adjustments according to actual conditions during selection.)

### Calculation of Electric Cylinder Service Life

The service life of an electric cylinder generally refers to the service life of the lead screw used inside the electric cylinder, which can be divided into three parts:a. Operational Service Life, It depends on the operating conditions of the electric cylinder, such as operating intensity, operating environment, type of lubrication, and frequency of post-operation maintenance, etc;b. Accuracy Service Life, It refers to the accuracy deterioration caused by wear;c. Fatigue Life of the Lead Screw, It can be obtained through the calculation of the lead screw's fatigue life. The following is the calculation method for the fatigue life of the electric cylinder.

$$L_s = \left(\frac{Ca}{Fm \times fw}\right)^3 X L$$

Load Factor (fw)							
Vibration and Shock	fw						
Light	V<15 (m/min)	1.0~1.2					
Medium	15 <v<60 (m="" min) <="" td=""><td>1.2~1.5</td></v<60>	1.2~1.5					
Heavy	V>60 (m/min)	1.5~3.0					


Ls: Electric Cylinder Service Life (km)

Fm: Axial Average Load Borne by Electric Cylinder (kN)

Ca: Basic Dynamic Load Rating of Lead Screw Nut (kN) <Please refer to the specific performance indicators of the lead screw>

### Calculation of Average Axial Load for Electric Cylinder

When the axial load is constantly changing, to determine the fatigue life, it is necessary to first calculate the axial average load (Fm). For the electric cylinder, the force, speed, and time in different working sections within one working cycle are analyzed as follows:



The calculation formula for the axial average load of the electric cylinder is as follows:

$$F_{m} = \left(\frac{F_{1}^{3} \times v_{1} \times t_{1} + F_{1}^{3} \times v_{2} \times t_{2} + F_{3}^{3} \times v_{3} \times t_{3} + F_{4}^{3} \times v_{4} \times t_{4}}{1 \times t_{1} + v_{2} \times t_{2} + v_{3} \times t_{3} + v_{4} \times t_{4}}\right)^{\frac{1}{3}}$$

# Electric Cylinder Selection Table

		Electric Cylinder S	Selection	Table	
Serial Number	Customer Requirements	Customer Name (Customer Code		Industry	
NO.	Requirements	Selection	Code	Fill in the content	Notes
1	Electric Cylinder Stroke:	Lmax = mm			Stroke Requirements
2	Electric Cylinder Load:	mmax = kg			Maximum Load
3	Electric Cylinder Speed:	Vmax = mm/s			Maximum Speed
4	Electric Cylinder Precision:	± mm			Repeat Positioning Accuracy
5	Usage Frequency	f=			Accuracy Operation Times per Day
		Direct Mounting	ВС		
6	Motor Mounting Method:	Folding Installation	BR		
		Vertical Mounting	ВМ		
		Flangeless	F		
		Front Flange	FA		
7	Electric Cylinder Mounting Method:	Side Flange	LB		
7		Rear Flange	FB		
		Rear Hinge	CA/CB		
		Rear Flange	TC/TB		
		External Thread	Α		
		Internal Thread	В		
		Rod End Bearing	G		
	Front-End Mounting	Y-Type Connector/Adapter	Υ		
8	Methods of Electric Cylinders	I-Type Connector/Adapter	I		
		Ball Joint	Q		
		Flange	F		
		Pin Hole	R		
		Servo	AC/DC: SF		
0	Motor Selection	Stepper	BJ		Fill in: Motor Type, Motor Brand, DC/
9	WOLD SELECTION	Brushless DC	ZL		AC, Motor Power, Motor Size
		AC Constant Speed	JL		
10	Speed Reducer	Model/Ratio			Brand, Spur Gear/ Helical Gear
11	Limit Switch	Magnetic/Proximity	NPN/PNP		Brand
12	Others	Anti-Corrosion/High-Low Temperature (Resistant)/Explosion-Proof/Waterproof			
13	System Configuration	Basic/Standard/Advanced			

# Memorandum



Email: sales@wodtop.com Phone: 0755-23732760

Specifications are subject to change without prior notice. All rights reserved. No text or images may be reproduced or imitated without the

company's consent.

